

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1-12. (Canceled)

13. (Currently Amended) A magnetoresistive effective element comprising a first shielding layer, a second shielding layer, a magnetoresistive effective film, a first gap film, a pair of second gap layers, a pair of magnetic domain controlling layers, and a bottom electrode layer,

said first shielding layer and said second shielding layer being separated by a given distance,

said magnetoresistive effective film being disposed in between said first shielding layer and said second shielding layer,

said first gap film being made of electrical conductive material, and formed on said magnetoresistive effective film commensurate with a surface configuration of said magnetoresistive effective film,

said magnetic domain controlling layers ~~surround~~ surrounding and ~~extend~~ extending along both sides of said magnetoresistive effective film, respectively,

said bottom electrode layer being electrically connected to said magnetoresistive effective film on a side away from said first gap film, the bottom electrode layer constituting one of the pair of second gap layers,

said second shielding layer functioning as a top electrode layer electrically connected to said first gap film, and the second shielding layer constituting the other of the pair of second gap layers,

wherein a total thickness of said magnetoresistive effective film and said~~the~~
first gap film is ~~thicker~~ larger than a thickness of the magnetic domain controlling layers to
suppress the effects of a defective side ~~lobe~~, lobe, and
surfaces of said second shielding layer corresponding to said magnetic domain
controlling layers extending along both sides of said magnetoresistive effective film are
formed closer to said bottom electrode layer than a surface of said magnetoresistive effective
film on which said first gap film is formed.

14. (Original) The magnetoresistive effective element as defined in claim 13,
wherein said magnetoresistive effective film is made of a spin valve film or a ferromagnetic
tunnel junction film.

15. (Previously Presented) The magnetoresistive effective element as defined in
claim 13, wherein said first gap film is made of metal.

16. (Canceled)

17. (Previously Presented) The magnetoresistive effective element as defined in
~~claim 16,~~ claim 13, wherein both sides of said second shielding layer are depressed at both
sides of the magnetoresistive effective film in a front view, respectively.

18-26. (Canceled)